



Product Catalogue

Lubricants for cars and trucks.
Range from July 2019



Clean technology protects your engine!



For generations, we have been developing products with the best possible protection for your machinery and components. We do everything we can to make sure you will also be able to rely on the quality and safety of our products in future.

The new XMF[®] technology has already proven its worth in our Aral Turboral engine oils for heavy-duty applications. This exclusive eXtra-Motorschutz-Formel is now also available for passenger car engines. The use of XMF[®] technology makes Aral Tronic passenger car engine oils more resilient and notably reduces deposits and abrasion. This means engines are kept cleaner and are protected against wear and tear – something that has been clearly and impressively demonstrated in standard engine tests.



You can learn more about **eXtra-Motorschutz-Formel XMF[®]** by watching the technology video at www.aral-lubricants.de/xmf

Engine Oils			
for Passenger Cars	Page	for Heavy Trucks	Page
Aral EcoTronic F 5W-20	4	Aral SuperTurboral 5W-30	7
Aral SuperTronic 0W-40	4	Aral SuperTurboral LA 5W-30	7
Aral SuperTronic E 0W-30	4	Aral MegaTurboral LA 10W-40	7
Aral SuperTronic G 0W-40	4	Aral MegaTurboral 10W-40	8
Aral SuperTronic LL IV FE 0W-20	4	Aral MegaTurboral VR 10W-40	8
Aral SuperTronic LongLife III 5W-30	5	Aral Turboral 10W-40	9
Aral HighTronic C 5W-30	5	Aral Turboral 15W-40	9
Aral HighTronic F 5W-30	5	Aral Turboral 10W	9
Aral HighTronic G 5W-30	5	Aral Turboral 20W-20	9
Aral HighTronic J 5W-30	5	Aral Turboral 20W-50	9
Aral HighTronic R 5W-30	6	Aral Turboral 30, 40	10
Aral HighTronic 5W-40	6	Aral Traktoral 10W-40	10
Aral HighTronic M 5W-40	6		
Aral BlueTronic 10W-40	6		
Aral Tronic 15W-40	6		

Driveline Fluids for Cars and Heavy Trucks			
Automatic Transmission Fluids	Page	Manual Transmission Fluids	Page
Aral Getriebeöl ATF M 14	11	Aral Getriebeöl SNS-M 75W-80	12
Aral Getriebeöl ATF LD	11	Aral Getriebeöl SNS 75W-80	12
Aral Getriebeöl ATF J	11	Aral Getriebeöl SNS-A 75W-85	12
Aral Getriebeöl ATF 55	11	Aral Getriebeöl SNS-AT 75W-90	12
Aral Getriebeöl ATF 22	11	Aral Getriebeöle EP SYNTH 75W-90	13
		Aral Getriebeöle EP 80W	13
		Aral Getriebeöle EP 80W-90	13
		Aral Fluid HGS 80W	13
		Aral Fluid T0-4 10W, 30	13
Rear Axle Fluids	Page	Rear Axle Fluids	Page
Aral Getriebeöl BS 75W-90	14	Aral Getriebeöle HYP 85W-90, 85W-140	15
Aral Getriebeöl SNA-C 75W-90	14	Aral Getriebeöl BS-LSX 75W-140	15
Aral Getriebeöl HYP SYNTH 75W-90	14	Aral Getriebeöl HYP LS 85W-90	15
Aral Getriebeöl SNA-D 80W-90	14	Aral Getriebeöl SNA-E 75W-90	15
		Aral Getriebeöl EP Plus 80W-90	15

Specialities			
Antifreeze	Page	Greases	Page
Aral Antifreeze Silikatfrei	16	Aral Mehrzweckfett	16
Aral Antifreeze Extra	16	Aral Mehrzweckfett F	16
		Aral Langzeitfett H	16
		Aral Radlagerfett	16
		Aral Fließfett N	16

for Passenger Cars

Article No. Aral	Capacity	Container	EAN Code
Aral EcoTronic F 5W-20	API SN • Meets Ford WSS-M2C948-B • IISAC GF-5		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	4 l	canister	country-specific
country-specific	1 l	small packages	country-specific

Aral EcoTronic F 5W-20 is a high-performance engine oil in Aral Synthetic-Technology specially engineered for Ford EcoBoost® engines that need an oil according to Ford WSSM2C948- B. It is also suitable for use in most modern Ford petrol engines that require an oil according to Ford WSS-M2C913-B, WSS-M2C913-C or WSS-M2C925-B (with the exception of Ford Ka, Focus ST and Focus RS). Also suitable for Asian and American manufacturers that require engine oil according to performance standard API SN or lower. For all vehicles that want to benefit by this engine oil of low viscosity grade SAE 20 in combination with high-quality Synthetic-Technology for fuel savings and protection against wear (please observe manufacturer specifications). Meets all XMF performance requirements.



Article No. Aral	Capacity	Container	EAN Code
Aral SuperTronic 0W-40	API SN/CF • MB-Approval 229.31/ 229.51 • Meets Fiat 9.55535-S2		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	20 l	canister	country-specific
country-specific	4 l	canister	country-specific
country-specific	1 l	small packages	country-specific

Fully synthetic high performance engine oil for petrol and diesel engines with and without diesel particle filter. Meets all XMF performance requirements.

- Universally applicable with an extensive approval profile
- Aral Low SAPS-Technology maximizes diesel particle filter lifespan
- Safety for the engine at extended drain intervals
- Lower fuel consumption of approximately 3 % and improved emissions performance



Article No. Aral	Capacity	Container	EAN Code
Aral SuperTronic E 0W-30	ACEA A5/B5 • API SL/CF		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	4 l	canister	country-specific
country-specific	1 l	small packages	country-specific

High performance engine oil in Aral Synthetic-Technology. Meets all XMF performance requirements.

- For petrol and diesel engines in cars, e.g. from Volvo, Honda and Renault, that require engine oils as per ACEA A5/B5
- For extended drain intervals for certain Volvo models



Article No. Aral	Capacity	Container	EAN Code
Aral SuperTronic G 0W-40	ACEA A3/B3, A3/B4 • API SN/CF • MB-Approval 226.5/ 229.3/ 229.5 • VW 502 00/ 505 00 • Porsche A40 • Renault RN0700 / RN 0710		
country-specific	bulk*		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	4 l	canister	country-specific
country-specific	1 l	small packages	country-specific

Aral SuperTronic G SAE 0W-40 is a high-performance engine oil in Aral Synthetic-Technology with excellent low-friction characteristics. Meets all XMF performance requirements.

- Optimal cold-start properties
- Especially for petrol and diesel engines for Mercedes-Benz, VW and Renault
- Provides longest oil drain intervals at flexible service cycles
- Reduces fuel requirements and oil consumption
- Fulfills the most rigorous anti-wear standards



Article No. Aral	Capacity	Container	EAN Code
Aral SuperTronic LL IV FE 0W-20	VW 508 00/ 509 00		
country-specific	208 l.	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	20 l	canister	country-specific
country-specific	5 l	canister	country-specific
country-specific	1 l	small package	country-specific

Fully synthetic high-performance engine oil for passenger cars: For gasoline or diesel engines

- Provides an outstanding anti-wear performance
- Designed for longest drain intervals at flexible maintenance periods
- Provides less fuel and oil consumption

Aral SuperTronic LL IV FE 0W-20 is suitable for use in automotive gasoline and diesel engines in vehicles from the VW group where the manufacturer recommends a VW 508 00, 509 00 specification 0W-20 lubricant.



for Passenger Cars			
Article No. Aral	Capacity	Container	EAN Code
Aral SuperTronic LongLife III 5W-30	ACEA C3 • MB-Freigabe 229.51 • VW 504 00/ 507 00 (meets the technical requirements of former VW standard 503 01) • Porsche C30		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	20 l	canister	country-specific
country-specific	5 l	canister	country-specific
country-specific	4 l	canister	country-specific
country-specific	1 l	small packages	country-specific
<p>High performance engine oil especially for VW Group cars¹⁾ (VW, Audi, SEAT and Škoda). For petrol and diesel engines. Meets all XMF performance requirements.</p> <ul style="list-style-type: none"> • Fulfills the most rigorous anti-wear standards • Aral Low SAPS-Technology for maximum diesel particle filter service life • Suitable for vehicles with and without LongLife service <p>¹⁾ With the exception of R5 and V10 TDI unit injector engines in the Phaeton, Touareg and T5 models and certain unit injector engines without LongLife service or DPf. Please consult user's manual!</p>			
Aral HighTronic C 5W-30	ACEA C1 • Jaguar Land Rover engine oil specification STJLR.03.5005		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	4 l	canister	country-specific
country-specific	1 l	small packages	country-specific
<p>High performance engine oil in Aral Synthetic-Technology. Meets all XMF performance requirements.</p> <ul style="list-style-type: none"> • Developed particularly for passenger cars with diesel particle filters requiring an ACEA C1 or C2 compliant engine oil • With Aral low SAPS-Technology to help maximize life span of diesel particle filters 			
Aral HighTronic F 5W-30	ACEA A1/B1, A5/B5 • API SL/CF • ILSAC GF-4 • Meets Ford WSS-M2C913-A, WSS-M2C913-B, WSS-M2C913-C, WSS-M2C913-D		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	4 l	canister	country-specific
country-specific	1 l	small packages	country-specific
<p>High performance engine oil in Aral Synthetic-Technology especially for cars from Ford, Chrysler, Jaguar and Land Rover. Meets all XMF performance requirements.</p> <ul style="list-style-type: none"> • For petrol and diesel engines 			
Aral HighTronic G 5W-30	ACEA C3 • API SN/CF • MB-Approval 229.31/ 229.51/ 229.52 • BMW Longlife-04		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	20 l	canister	country-specific
country-specific	5 l	canister	country-specific
country-specific	4 l	canister	country-specific
country-specific	1 l	small packages	country-specific
<p>High performance engine oil in Aral Synthetic-Technology. Meets all XMF performance requirements.</p> <ul style="list-style-type: none"> • Modern Aral Low SAPS-Technology for a maximum life-circle and protection of particle filter as well as catalytic converters 			
Aral HighTronic J 5W-30	ACEA C2 • PSA B71 2290		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	4 l	canister	country-specific
country-specific	1 l	small packages	country-specific
<p>High performance engine oil in Aral Synthetic-Technology. Meets all XMF performance requirements.</p> <ul style="list-style-type: none"> • Especially for vehicles from French and Asian manufacturers that require engine oil as per ACEA C2 specification. • Modern Aral Low SAPS-Technology for a maximum life-circle and protection of particle filter as well as catalytic converters 			

for Passenger Cars			
Article No. Aral	Capacity	Container	EAN Code
Aral HighTronic R 5W-30	ACEA C4 • MB-Approval 226.51 • Renault RN0720		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	4 l	canister	country-specific
country-specific	1 l	small packages	country-specific
<p>High performance engine oil in Aral Synthetic-Technology. Meets all XMF performance requirements.</p> <ul style="list-style-type: none"> • Especially for all modern Renault diesel models also with particle filters. • Modern Aral Low SAPS-Technology for a maximum life-circle and protection of particle filter as well as catalytic converters 			
Aral HighTronic 5W-40	ACEA C3 • API SN/CF • MB-Approval 229.31/ 229.51 • VW 505 00/ 505 01 • GM dexos2® • Meets Ford WSS-M2C917-A • Meets Fiat 9.55535-S2 • Renault RN0700 / RN0710 • Porsche A40		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	20 l	canister	country-specific
country-specific	5 l	canister	country-specific
country-specific	4 l	canister	country-specific
country-specific	1 l	small packages	country-specific
<p>High performance engine oil in Aral Synthetic-Technology for demanding driving conditions. Meets all XMF performance requirements.</p> <ul style="list-style-type: none"> • For petrol and diesel engines • Modern Aral Low SAPS-Technology for a maximum life-circle and protection of particle filter as well as catalytic converters • High power reserves in engines with extended drain intervals and minimal top up requirement • Saves fuel and protects the environment 			
Aral HighTronic M 5W-40	ACEA A3/B3, A3/B4 • API SN/CF • MB-Approval 229.3/ 229.5/ 226.5 • VW 502 00/ 505 00 • BMW Longlife-01 • Porsche A40 • Renault RN0700 / RN0710		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	20 l	canister	country-specific
country-specific	5 l	canister	country-specific
country-specific	4 l	canister	country-specific
country-specific	1 l	small packages	country-specific
<p>High performance engine oil in Aral Synthetic-Technology for demanding driving conditions. Ash-based formula with premium additives. Meets all XMF performance requirements.</p> <ul style="list-style-type: none"> • For Mercedes Benz cars with petrol engines and all diesel engines without particle filters • For petrol and diesel engines, including those made by BMW and the VW Group 			
Aral BlueTronic 10W-40	ACEA A3/B4 • API SN • MB-Approval 229.1 • Meets Fiat 9.55535-D2 • VW 501 01/ 505 00		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	20 l	canister	country-specific
country-specific	5 l	canister	country-specific
country-specific	4 l	canister	country-specific
country-specific	1 l	small packages	country-specific
<p>Low-friction engine oil in Aral Synthetic-Technology.</p> <ul style="list-style-type: none"> • For petrol and diesel engines 			
Aral Tronic 15W-40	ACEA A3/B3 • API SN • MB-Approval 229.1 • Meets Fiat 9.55535-D2		
country-specific	208 l	drum	country-specific
country-specific	4 l	canister	country-specific
country-specific	1 l	small packages	country-specific
<p>Multipurpose oil with selected mineral oil.</p> <ul style="list-style-type: none"> • For use in petrol and diesel engines 			

for Heavy Trucks				
Article No. Aral	Capacity	Container	EAN Code	
Aral SuperTurboral 5W-30	ACEA E4, E7 • MB-Approval 228.5 • Volvo VDS 3 • Scania LDF-3 • RVI RLD-2 • MTU Ölkategorie 3 • Cummins CES 20077 • Deutz DQC III-10 • Mack EO-N • MAN M 3277			
country-specific	bulk			<p>Low-friction engine oil in Aral Synthetic-Technology for use in almost all commercial vehicles from European manufacturers. Meets all XMF performance requirements.</p> <ul style="list-style-type: none"> • Average fuel savings of 4% in contrast to an oil with a viscosity of 15W-40 (proven in numerous fleet tests) • For extended drain intervals up to 150,000 km (please observe manufacturer specifications!) • Optimal cold-start properties • Outstanding results for the reduction of deposits in turbochargers and intercoolers • More protection against wear for long engine service life • Optimal power reserves, even for diesel fuels with high sulphur content (e.g. in countries with poor fuel quality) <p>Must not be used in petrol cars!</p>
country-specific	208 l	drum	country-specific	
country-specific	60 l	EGF	country-specific	
country-specific	20 l	canister	country-specific	
country-specific	4 l	canister	country-specific	
Aral SuperTurboral LA 5W-30	ACEA E6, E7, E9 • API CJ-4 • MB-Approval 228.51 • MAN M 3677, M 3477, M 3271 • Volvo VDS 3, VDS 4 • Scania Low Ash • RVI RLD-3 RXD • Meets DAF requirements • Deutz DQC IV-10LA • CAT ECF-3 • JASO DH-2 • Mack EO-M Plus, EO-N, EO-O Premium Plus • Cummins CES 20081 • MTU Ölkategorie 3.1			
country-specific	bulk			<p>Aral SuperTurboral LA 5W-30 is an engine oil in Aral Synthetic-Technology for use in almost all commercial vehicles from European manufacturers that require a low SAPS engine oil. The unique Aral Synthetic-Technology delivers the cleanest engine lubricating system possible. It can be used for Euro 3, Euro 4, Euro 5 and Euro 6 engines, even for temperatures below -30°C, for the longest drain intervals (please observe manufacturer specifications!). Meets all XMF performance requirements.</p> <ul style="list-style-type: none"> • Excellent low-temperature properties deliver rapid engine lubrication, which in turn minimises wear • Enables the exhaust after-treatment systems to function optimally, even at extremely low temperatures • Outstanding engine cleanliness due to minimised deposits and an optimised detergent system lead to an extended drain interval (Please observe manufacturer specifications!) and thus a reduction operating costs • Fuel savings potential by means of a reduction in interior friction <p>Must not be used in petrol cars!</p>
country-specific	208 l	drum	country-specific	
country-specific	60 l	EGF	country-specific	
country-specific	20 l	canister	country-specific	
country-specific	4 l	canister	country-specific	
Aral MegaTurboral LA 10W-40	ACEA E6, E7, E9 • API CJ-4 • MB-Freigabe 228.51 • RVI RLD-3 • MAN M 3477, M 3271-1 • Volvo CNG, VDS 4, VDS 4.5 • Cummins CES 20081 • Meets DAF requirements • Deutz DQC IV-10LA • MTU Ölkategorie 3.1 • CAT ECF-3 • JASO DH-2 • Mack EO-O Premium Plus, EOS-4.5 • can be used for Iveco Trucks that required for ACEA E6, E7, E9			
country-specific	bulk			<p>Aral MegaTurboral LA makes a significant contribution to meeting the rigorous Euro 4, Euro 5 and Euro 6 directives. And this high-performance diesel engine oil also prevents deposits on pistons, piston rings, cams, rocker arms and all other highly stressed engine parts to a significant extent. The minimised proportion of sulphated ash, phosphorus and sulphur (low SAPS engine oil) ensures that Aral MegaTurboral LA can be used in Euro 5 engines with diesel particle filters. Meets all XMF performance requirements.</p> <ul style="list-style-type: none"> • Optimises the effectiveness of exhaust after-treatment to comply with the legally stipulated Euro 4, Euro 5 and Euro 6 limits • Enables the longest possible drain intervals • Minimises wear and extends equipment service life • Contains detergent additives that prevent deposits over the long term and deliver excellent engine cleanliness • Reduces the risk of oil thickening through dispersing additives and a high sludge-handling ability <p>Must not be used in gasoline engines. Please refer to owner's manual.</p>
country-specific	1.000 l	drum	country-specific	
country-specific	208 l	drum	country-specific	
country-specific	60 l	EGF	country-specific	
country-specific	20 l	canister	country-specific	
country-specific	4 l	canister	country-specific	

for Heavy Trucks

Article No. Aral	Capacity	Container	EAN Code
Aral MegaTurboral 10W-40	ACEA E4/E7 • API CI-4 • MB-Approval 228.5 • MAN M 3277 • Volvo VDS 3 • RVI RLD-2 • Cummins CES 20077, CES 20078 • JASO DH-1 • MTU Ölkategorie 3 • Mack EO-N • DDC Power Guard 93K215 • Deutz DQC III-10		
country-specific	bulk		
country-specific	950 l	drum	country-specific
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	20 l	canister	country-specific
country-specific	5 l	canister	country-specific

Low-friction engine oil in Aral Synthetic-Technology for diesel engines approved for extended drain intervals. Meets the rigorous requirements of commercial-vehicle manufacturers and the equally rigorous European test requirements. Not suitable for Euro 4 or Euro 5 vehicles that require a low SAPS engine oil. Meets all XMF performance requirements.

- Minimal wear due to load-bearing oil film, even under extreme thermal stress and mechanical loads
- Excellent cold-start performance
- High power reserves, also for diesel fuels with high sulphur content
- Enables extended drain intervals up to 120,000 km (please observe manufacturer specifications!)

Must not be used in petrol cars!



Article No. Aral	Capacity	Container	EAN Code
Aral MegaTurboral VR 10W-40	ACEA E9 • API CJ-4 • MB-Approval 228.31 • MAN M 3275 • Volvo VDS 4 • RVI-RLD, RVI RLD-3 • Deutz DQC III-10LA • CAT ECF-3 • Cummins CES 20081 • Mack EO-O Premium Plus		
country-specific	bulk*		
country-specific	208 l*	drum	country-specific
country-specific	60 l*	EGF	country-specific
country-specific	20 l*	canister	country-specific

Aral Mega VR 10W-40 is a low SAPS diesel engine oil for commercial vehicles that require a lubricant as per ACEA E9 and/or API CJ-4. This product was developed for commercial vehicles – on-road and off-road – that are equipped with diesel particle filters and therefore require a low SAPS engine oil. It is particularly useful for Volvo, Renault, Caterpillar and Cummins engines in commercial vehicles for longest drain intervals (please observe manufacturer specifications!). Meets all XMF performance requirements.

- The Aral Synthetic-Technology components enable the longest drain intervals (according to manufacturer specifications), even under extremely harsh conditions and therefore reduce maintenance and the resulting standstill time and costs
- Minimises wear, protects engines and extends engine service life
- Due to the use of low SAPS-Technology, it optimises the effectiveness of exhaust after-treatment and therefore guarantees assured compliance with the legally stipulated emission limits
- Contains additives with outstanding detergent properties that prevent deposits on a long term basis and deliver excellent engine cleanliness

Must not be used in petrol cars!



for Heavy Trucks			
Article No. Aral	Capacity	Container	EAN Code
Aral Turboral 10W-40	ACEA E7 • API CI-4/SL • MB-Approval 228.3 • MAN M 3275-1 • Volvo VDS 3 • RVI RLD-2 • Deutz DQC III-10 • MTU Ölkategorie Typ 2 • CAT ECF-2 • Cummins CES 20077, CES 20078 • Mack EO-M Plus, EO-N • DDC Power Guard 93K215		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	20 l	canister	country-specific
country-specific	5 l	canister	country-specific
country-specific	1 l	small packages	country-specific
<p>Low-friction engine oil in Aral Synthetic-Technology for mixed fleets with both diesel and internal combustion engines. With extremely high-performance additives and fuelsavings potential, plus a very broad range of applications. Meets all XMF performance requirements.</p> <ul style="list-style-type: none"> • Reduction in logistics costs due to simplified warehouse storage • Good cold-start performance and rapid supply of oil to the engine • Effective prevention of cold sludge and black sludge • Meets rigorous engine cleanliness requirements 			
Aral Turboral 15W-40	ACEA E7 • API CI-4/SL • MB-Approval 228.3 • Meets requirements of MAN M 3275-1 • Volvo VDS 3 • RVI RLD-2 • CAT ECF-2 • Cummins CES 20077, CES 20078 • MTU Ölkategorie 2 • Deutz DQC III-10 • MACK EO-M Plus, EO-N • DDC Power Guard 93K215		
country-specific	bulk		
country-specific	1000 l	drum	country-specific
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	20 l	canister	country-specific
country-specific	5 l	canister	country-specific
country-specific	1 l	small packages	country-specific
<p>Mineral-oil-based engine oil with outstanding performance capacity and an additive package designed especially for use in commercial vehicles. Meets all XMF performance requirements.</p>			
Aral Turboral 10W	API CF		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	20 l	canister	country-specific
<p>Mineral-oil-based, single-purpose engine oil with high-performance additives. For use with hydraulic clutches, retarders and transmissions (please check manufacturer specifications!).</p>			
Aral Turboral 20W-20	API CF/SF • MB-Approval 228.0/ 235.27 • Voith Retarder Ölklasse A		
country-specific	bulk*		
country-specific	208 l*	drum	country-specific
country-specific	20 l*	canister	country-specific
<p>Mineral-oil-based, single-purpose engine oil with high-performance additives. For use with hydraulic clutches, retarders and transmissions (Please consult manufacturer handbook!).</p>			
Aral Turboral 20W-50	API CH-4		
country-specific	208 l	drum	country-specific
country-specific	20 l	canister	country-specific
country-specific	5 l	canister	country-specific
country-specific	1 l	small packages	country-specific

for Heavy Trucks			
Article No. Aral	Capacity	Container	EAN Code
Aral Turboral 30			
API CF			
country-specific	bulk*		
country-specific	208 l	drum	country-specific
country-specific	20 l	canister	country-specific
Mineral-oil-based, single-purpose engine oil with high-performance additives. For use with hydraulic clutches, retarders and transmissions (Please consult manufacturer handbook!).			
Aral Turboral 40			
API CF/CF-2			
country-specific	208 l	drum	country-specific
country-specific	20 l	canister	country-specific
Mineral-oil-based, single-purpose engine oil with high-performance additives. For use with hydraulic clutches, retarders and transmissions (Please consult manufacturer handbook!).			
Aral Traktoral 10W-40			
ACEA E2 • API CF-4/SF/GL-4 • ZF TE-ML 06D, MF M1145 • Meets MF M1144, M1139 • meets JDM J27 • Meets Ford ESN-M2C159-B • can be used if the following specifications are recommended: JD J20C, Case MS1207, Ford M2C134-D, M2C86-B			
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	20 l	canister	country-specific
Type STOU mineral-oil-based, all-purpose tractor oil. Thanks to all-purpose properties, it is suitable for engines (SDI and turbo diesel), transmissions (in particular, with wet brakes) and hydraulics. Safe and economical with top viscosity performance and high protection against wear (Please consult manufacturer handbook!).			

Automatic Transmission Fluids			
Article No. Aral	Capacity	Container	EAN Code
Aral Getriebeöl ATF M 14	MB-Approval 236.14		
country-specific	208 l	drum	country-specific
country-specific	20 l	canister	country-specific
Transmission fluid for use in automatic car transmissions as per current MB specifications and GM specification with fuel savings potential.			
Aral Getriebeöl ATF LD	ZF TE-ML 04D, 11B, 14C, 16M, 16S, 20C, 25C • Voith H55.6336.xx • MB-Approval 236.81 • MAN 339 TYP V2, Z3, Z12		
country-specific	208 l	drum	country-specific
country-specific	20 l	canister	country-specific
Fully synthetic fluid for automatic and power-shift transmissions and hydraulic plants in the automotive and industry sectors. Specially developed for extended drain intervals in the automatic transmissions of certain trucks and buses. <ul style="list-style-type: none"> • Particularly advantageous for use in mixed commercial-vehicle fleets with transmission systems from Allison, Mercedes-Benz, Voith and ZF • Unique low-temperature properties and high friction value stability assure high levels of operating safety, shifting comfort and protection against wear for critical parts of modern automatic transmissions 			
Aral Getriebeöl ATF J	JASO 1A		
country-specific	bulk		
country-specific	20 l	canister	country-specific
country-specific	1 l	small packages	country-specific
Automatic transmission fluid in Aral Synth Technology for use in most Asian passenger cars. Please refer to owner's manual.			
Aral Getriebeöl ATF 55	ZF TE-ML 04D, 14A • Voith H55.6335.xx • MB-Approval 236.9 • MAN 339 Typ L1, V1, Z1 • Volvo Transmission Oil 97340, 97341:016 • meets MERCON® • meets DEXRON®-IIIH • Allison C4		
country-specific	bulk*		
country-specific	208 l*	drum	country-specific
country-specific	60 l*	EGF	country-specific
country-specific	20 l*	canister	country-specific
country-specific	1 l*	small packages	country-specific
Recommended for use in all Ford (1983-2003) and GM (before 2007) automatic transmissions. Do not use where Ford Type F, MERCON® V, MERCON® SP or DEXRON® VI fluids are required. Refer to owners' manual.			
Aral Getriebeöl ATF 22	ZF TE-ML 04D, 11A, 14A • Voith H55.6335.xx • MB-Approval 236.6 • MAN 339 Typ L2, V1, Z1 • meets MERCON® • meets DEXRON®-IID		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	20 l	canister	country-specific
country-specific	1 l	small packages	country-specific
country-specific	0,5 l	small packages	country-specific
Gear oil for automatic transmissions (former DEXRON®-IID). Please refer to owners' manual.			



Manual Transmission Fluids			
Article No. Aral	Capacity	Container	EAN Code
Aral Getriebeöl SNS-M 75W-80	API GL-4 • ZF TE-ML 01E, 02E, 16P • MB-Approval 235.41 • MAN 341 Typ Z5		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	20 l	canister	country-specific
<p>Aral SNS-M 75W-80 is particularly recommended for commercial vehicles (trucks, buses and small transporters) with standard transmissions that require an API class GL-4 fluid.</p> <ul style="list-style-type: none"> • Outstanding temperature and ageing stability deliver excellent system cleanliness • Excellent EP performance also enables maximum component protection, even with extreme loads • Distinct temperature reduction due to minimised friction extends the transmission service life • Optimal viscosity/temperature performance for improved shifting ability – can also be used at temperatures as low as –40°C 			
Aral Getriebeöl SNS 75W-80	API GL-4 • ZF TE-ML 01L, 02L, 16K • MAN 341 Typ Z4		
country-specific	208 l	drum	country-specific
country-specific	20 l	canister	country-specific
<ul style="list-style-type: none"> • The high-pressure transmission fluid in Aral Synthetic-Technology • For use in manual transmissions with and without interarders, in mechanical transmissions and steering systems • Also used in commercial vehicles for extended drain intervals (Please consult manufacturer handbook!) 			
Aral Getriebeöl SNS-A 75W-85	API GL-4 • MB-Approval 235.4 • MAN 341 TYP E4 • Volvo Transmission Oil 97307		
country-specific	208 l	drum	country-specific
country-specific	20 l	canister	country-specific
<p>Fully synthetic high-performance manual transmission fluid with high thermal stability. Specially developed for commercial vehicles, it enables a significant extension of drain intervals (please observe manufacturer specifications!).</p> <ul style="list-style-type: none"> • The SAE 75W-85 viscosity grade guarantees excellent shifting properties – even at extremely low temperatures – and its low-friction properties contribute to fuel savings • Suitable for all manual transmissions that require an API class between GL-1 and GL-4 			
Aral Getriebeöl SNS-AT 75W-90	API GL-4 • MB-Approval 235.11		
country-specific	208 l	drum	country-specific
country-specific	20 l	canister	country-specific
<p>Fully synthetic high-performance transmission fluid for manual transmissions in commercial vehicles. Particularly suitable for use in Mercedes-Benz vehicles in the Actros, Axor and Atego series.</p> <ul style="list-style-type: none"> • Multiple range viscosity enables year-round use • For use at very low and also at very high temperatures • Great degree of operating safety under all conditions 			

Manual Transmission Fluids			
Article No. Aral	Capacity	Container	EAN Code
Aral Getriebeöl EP SYNTH 75W-90	API GL-4 + • VW 501 50		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	20 l	canister	country-specific
country-specific	1 l	small packages	country-specific
High-performance Aral Synthetic-Technology transmission fluid with low-friction characteristics. • Multipurpose character SAE 75W-90 for passenger car manual transmissions, two-wheel gearboxes and axle transmissions as well as commercial-vehicle transmissions (e.g. truck, construction machinery and agricultural equipment)			
Aral Getriebeöl EP 80W	API GL-4 • ZF TE-ML 17A • MB-Approval 235.1		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	20 l	canister	country-specific
Standard transmission fluid for manual and axle transmissions that require lubrication as per API GL-4.			
Aral Getriebeöl EP 80W-90	API GL-4 • ZF TE-ML 02B, 17A • MAN 341 Typ Z2		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	20 l	canister	country-specific
country-specific	1 l	small packages	country-specific
Standard transmission fluid for manual and axle transmissions that require lubrication as per API GL-4.			
Aral Fluid HGS 80W	API GL-4 • ZF TE-ML 03E, 05F, 17E, 21F • Volvo 97303 (WB 101) • MF M1145 • Meets Ford ESN-M2C134-D • meets John Deere J20C • can be used if the following specifications are recommended: Case 1207, 1209, MAT 3505, MAT 3525, MAT 3540, NH410B or Ford M2C86-B		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	20 l	canister	country-specific
Combined hydraulic/transmission fluid (type: UTTO). • For modern tractor units and commercial vehicles if a single lubricant is recommended for the hydraulic system, brakes and transmission • Reliable operation, even for heavy jobs			
Aral Fluid TO-4 10W	ZF TE-ML 03C • CAT TO-4 • Komatsu		
country-specific	208 l	drum	country-specific
All-purpose transmission fluid for construction machinery and agricultural machines. For use in power-shift transmissions, final drives, wet brakes and axle transmissions as per manufacturer specifications.			
Aral Fluid TO-4 30W	ZF TE-ML 03C, 07F • CAT TO-4 • suitable for use in Komatsu equipment		
country-specific	bulk		
country-specific	208 l	drum	country-specific
All-purpose transmission fluid for construction machinery and agricultural machines. For use in power-shift transmissions, final drives, wet brakes and axle transmissions as per manufacturer specifications.			



Rear Axle Fluids			
Article No. Aral	Capacity	Container	EAN Code
Aral Getriebeöl BS 75W-90	API GL-5 • ZF TE-ML 05A, 12B, 17B, 19C, 21A • MAN 342 Typ S1 • Scania STO 1:0 • BMW (non LS rear axles)		
country-specific	bulk		
country-specific	208 l	drum	country-specific
Fully synthetic hypoid transmission fluid for truck and car rear axles. Also for manual transmissions that require fluid as per API GL-5 (Scania).			
Aral Getriebeöl HYP SYNTH 75W-90	API GL-4, GL-5		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	20 l	canister	country-specific
<p>High-performance Aral Synthetic-Technology transmission fluid with low-friction properties.</p> <ul style="list-style-type: none"> • Multipurpose SAE 75W-90 transmission fluid for heavy-load (hypoid) live axles • For highly stressed transmissions (manual/axle transmissions) in the car, two-wheel gearbox and commercial vehicle areas (e.g. trucks, construction machinery, agricultural equipment) (please observe manufacturer specifications!) 			
Aral Getriebeöl SNA-D 80W-90	API GL-5 • ZF TE-ML 05A, 12L, 12M, 16B, 17B, 19B, 21A • MB-Approval 235.20 • MAN 342 Typ M3 • MAN 341 Typ GA1 • Scania STO 1:0		
country-specific	208 l	drum	country-specific
Multipurpose axle transmission fluid for heavy-load transmissions with hypoid, spiral or helical gearing, final drives – also with large offsets – and drive-lines. Further applications thanks to multipurpose properties. Aral Getriebeöl SNA-D meets the requirements of a variety of OEM for trucks, cars, transporters, buses and agricultural machinery.			

Rear Axle Fluids			
Article No. Aral	Capacity	Container	EAN Code
Aral Getriebeöl HYP 85W-90	API GL-5 • ZF TE-ML 16C, 17B, 19B, 21A • MB-Approval 235.0		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	20 l	canister	country-specific
country-specific	1 l	small packages	country-specific
Hypoid transmission fluid for use in final drive systems, transfer gearboxes, differential gears with final drives and transmissions in cars and commercial vehicles (please observe manufacturer specifications!).			
Aral Getriebeöl HYP 85W-140	API GL-5 • ZF TE-ML 05A, 12E, 16D, 21A		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	20 l	canister	country-specific
Standard transmission fluid as per API class GL-5 for final drives with large offsets operating under extreme loads. It can also be used for manual transmissions when expressly required by the manufacturer.			
Aral Getriebeöl BS-LSX 75W-140	API GL-5 • ZF TE-ML 05C, 12D, 16G, 21C • MB-Approval 235.61 • BMW LS rear axles		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	20 l	canister	country-specific
Fully synthetic hypoid transmission fluid with LS additive for use in cars with locked axle systems and in axles, manual transmissions and auxiliary equipment in commercial vehicles for extended drain intervals.			
Aral Getriebeöl HYP LS 85W-90	API GL-5 • ZF TE-ML 05C, 12C, 16E, 21C		
country-specific	208 l	drum	country-specific
country-specific	20 l	canister	country-specific
Hypoid transmission fluid with limited slip (LS) additive for use in blocked axle systems, transfer gearboxes, differential gears with final drives and transmissions in cars and commercial vehicles.			
Aral Getriebeöl SNA-E 75W-90	API GL-4/ GL-5/ MT-1 • SAE J2360 • MAN 341 Typ Z2, MAN 342 Typ S1 • MB-Approval 235.8 • Scania STO 1:0 • ZF TE-ML 02B, 05A, 12L, 12N, 16F, 17B, 19C, 21A		
country-specific	208 l	drum	country-specific
country-specific	20 l	canister	country-specific
Fully synthetic, all-purpose low-friction transmission fluid that exceeds international AP classifications GL-4 and GL-5 and is perfect for use along the entire drivetrain of modern commercial and construction vehicles.			
<ul style="list-style-type: none"> • Special additives and fully synthetic base oils deliver top oxidation stability, outstanding cold performance and excellent low-temperature shifting ability • Also suitable for long drain intervals • Low-friction characteristics save fuel and deliver economic and ecological benefits in comparison to conventional fluids 			
Aral Getriebeöl EP Plus 80W-90	API GL-4 /GL-5/ MT-1 • ZF TE-ML 02B, 05A, 12L, 12M, 16B, 17H, 19B, 21A • MAN 341 Typ Z2, MAN 342 Typ M2		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	20 l	canister	country-specific
High-performance transmission fluid with state-of-the-art additive technology for allpurpose use in commercial vehicles in hypoid axles operating under extreme loads, synchronised manual transmissions, auxiliary drives, steering gears, transfer gearboxes, etc. (Please consult manufacturer handbook!).			

Antifreeze			
Article No. Aral	Capacity	Container	EAN Code
Aral Antifreeze Silikatfrei	MB-Approval 325.3 • ASTM D4985, ASTM D3306 (I) • MAN 324 Typ SNF • BS 6580:2010		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	1 l	small packages	country-specific
Coolant concentrate with long-term effectiveness for modern engines – contains no nitrites, amines, phosphates or silicates. <ul style="list-style-type: none"> • Operating fluid for summer and winter • Depending on dilution with water, can achieve frost protection down to –40°C (40% antifreeze plus 60% water by volume provides frost protection down to –27°C) 			
Aral Antifreeze Extra	MB-Approval 325.0 • ASTM D3306 • BS 6580:2010 • MAN 324 Typ NF • ASTM D4985 • MTU MTL 5048 • JASO JIS K2234 • Deutz DQC CA-14		
country-specific	bulk		
country-specific	208 l	drum	country-specific
country-specific	60 l	EGF	country-specific
country-specific	20 l	canister	country-specific
country-specific	1 l	small packages	country-specific
Antifreeze as operating fluid for summer and winter. <ul style="list-style-type: none"> • Coolant concentrate without nitrites, amines and phosphates – with silicates • Depending on dilution with water, can achieve frost protection down to –40°C (40% antifreeze plus 60% water by volume provides frost protection down to –27°C) 			
Greases			
Article No. Aral	Capacity	Container	EAN Code
Aral Mehrzweckfett	DIN 51502 K2K-30 • MB-Approval 267.0		
country-specific	180 kg	fettdrum	country-specific
country-specific	50 kg	hobbock	country-specific
country-specific	18 kg	pail	country-specific
country-specific	5 kg	pail	country-specific
country-specific	0,4 kg	cartridge	country-specific
Smooth, lithium-saponified grease based on high-quality mineral oils with select ingredients. <ul style="list-style-type: none"> • Contains anti-wear, anti-ageing and anti-corrosion components • All-purpose lubricant/lubricating grease for a wide range of applications, including the car sector with automotive industry approval 			
Aral Mehrzweckfett F	DIN 51502 KPF2K-30		
country-specific	18 kg	pail	country-specific
country-specific	0,4 kg	cartridge	country-specific
Waterproof, lithium-saponified, all-purpose EP grease with a molybdenum disulphide additive (MoS ₂). <ul style="list-style-type: none"> • Outstanding fail-safe operation characteristics 			
Aral Langzeitfett H	DIN 51502 KP2K-20		
country-specific	180 kg	fettdrum	country-specific
country-specific	50 kg	hobbock	country-specific
country-specific	18 kg	pail	country-specific
country-specific	0,4 kg	cartridge	country-specific
Lithium-saponified, multipurpose grease with EP additive. <ul style="list-style-type: none"> • Particularly smooth and strong adhesive properties, with automotive industry approval • Contains highly effective anti-corrosion and anti-ageing additives 			
Aral Radlagerfett	DIN 51502 KP2N-30 • MB-Approval 265.1 • MAN 284 Li-H2 • NLGI 2		
country-specific	18 kg	pail	country-specific
Lithium-saponified complex grease for all types of wheel bearings and other lubrication points at high temperatures.			
Aral Fließfett N	DIN 51826 GP00K-40 • MB-Approval 264.0 • MAN 283 Li-P 00/000 • NLGI 00/000 • suitable for use in Vogel AG and Lincoln Lubrication Systems		
country-specific	18 kg	pail	country-specific
Lithium-saponified, partially synthetic semi-fluid grease for lubricating commercial vehicles with centralised lubrication systems.			

All you need: aral-lubricants.com

Responsive for all mobile devices

- up-to-date product and safety data sheets
- product catalogue with the latest approvals and specifications
- oil finder with search function
- and much more on www.aral-lubricants.com



Please ask your Aral representative for questions around order quantities, prices etc.

Aral Aktiengesellschaft
Geschäftsbereich Schmierstoffe
Überseeallee 1
20457 Hamburg

Tel. 0800/723 71 14*
inboundaral@bp.com
www.aral-lubricants.de
www.aral.de

*Charge free within Germany for all calls from fixed and mobile network.

Version PDF: July 2019

The content of this brochure meets current status of technology. Changes of technical data or instructions for use are subject to modifications and amendments.